UWC-330

- **STAINLESS STEEL HOUSING OR DELRIN HOUSING**
- **HIGH DEFINITION**
- **COLOR**
- **COMPACT SIZE**





USES INCLUDE: HELMET MOUNT, MANIP ARM, HAND-HELD, DROP CAMERA, ETC.

MECHANICAL:

Diameter	1.62 in. (41 mm)
Length (excluding connector)	5 in. (127 mm)
Weight in air (SS)	1.23 lbs. (0.56 kg)
Weight in seawater (SS)	0.63 lbs. (0.28 kg)
Weight in air (Plastic)	1.77 lbs. (0.24 kg)
Weight in seawater (Plastic)	0.11 lbs. (0.05 kg)
Depth Rating	6560 ft. (2000 m)
Housing Material	316 Stainless Steel or Delrin
Port Material	Acrylic (Options Available)

CAMERA PROPERTIES:

Image Device	½" Sony Sensor
Sensitivity	0.017 lux
Resolution	1080P
Focus	Fixed
Horizontal FOV (in air)	~80°
Standard Format	NTSC
Signal type	AHD

NOTE: TRANSMISSION DISTANCE LIMITED TO 330M (USING OUTLAND C-2300 CABLE).


ELECTRICAL:

Input Voltage	10-24 VDC
Power	135 mA (typical) @ 12 VDC

CONNECTOR:

Standard Connector	XSK-5-BCL
Mate for Standard Connector	RMK-5-FS

1. Video
2. Ground / Common
3. Power (+12V)
4. Not Connected
5. Not Connected



Looking at the male pins on the back of the camera

OPTIONS:

1. PAL Format
2. Port material
3. Housing Material
4. Customer-specified connector

38190 Commercial Ct, Slidell, LA 70458 USA | (985) 847-1104 | www.outlandtech.com

Doc #: 04-0003 Rev B6